



AUTOMATIC DIECUTTING & CREASING MACHINE



AUTOMATIC DIECUTTING & CREASING MACHINE

OUTSTANDING FEATURES

- New style feeder head for accurate feeding of various types and even difficult stock, all adjustments can be made on the run.
- Non-stop feeder with motorized side shift and non-stop delivery with counter and tape inserter to ensure continuous productivity.
- The slow down device on feed board allows sheet to enter head stopper at a greatly reduced speed to ensure excellent register when running thinner weight stock.
- Microprocessor assisted monitoring and self-diagnosis system for safe operation and easy maintenance. Control system with LCD screen display provides information of each section to facilitate operation and trouble shooting.
- Triple action stripping station with gripper edge removal device further enhances productivity.
- The slow down brush and double air bar system at delivery can all be adjusted on the run, and all can be turned off and on while the machine is in "RUN" mode.

ADDED FEATURES ON 1450SE

- Both pallets off printing press and pre-loading device can be used.
- Special pressing belts and rolls on feed board to ensure smooth feeding of warped litho-laminated boards.
- Upper stripping frame can be raised 350mm (14") for easy set up.

Hardening aluminum alloy feeding rollers ensure running thinner stock at higher speed



Non-stop delivery with tape inserter



Triple action stripping station



Non-stop feeder with pre-loading device, also taking pallet right off the press



Control system with LCD screen display



1050SE



1450SE



HEADQUARTERS
 #1 - 1500 Valmont Way
 Richmond, British Columbia
 Canada, V6V 1V4
 Tel: (604) 278-2027
 Fax: (604) 278-1005
 E-mail: printech@can.rogers.com



NORTHERN OFFICE
 #14 - 7700 68th Avenue North
 Brooklyn Park, MN
 55428 U.S.A.
 Tel: (763) 535-5885
 Fax: (763) 535-6660
 E-mail: north@brausse.com

EASTERN OFFICE
 476 Bergen Blvd., Suite 2B
 Ridgefield, NJ
 07657 U.S.A.
 Tel: (201) 941-1199
 Fax: (201) 941-0738
 E-mail: east@brausse.com

Max. sheet size:	1050 x 750 mm (41 1/8" x 29 1/2")	1450 x 1100mm (57" x 43-1/4")
Min. sheet size:	400 x 370 mm (15 3/4" x 14 1/2")	700 x 500 mm (27-1/2" x 19-3/4")
Max. cutting size:	1041 x 730 mm (41" x 28 3/4")	1420 x 1080 mm (56" x 42-1/2")
Min. gripper margin:	9 mm (23/64")	10 mm (25/64")
Inner chase size:	1145 x 755 mm (45" x 29 3/4")	1480 x 1106 mm (58-1/4" x 43-1/2")
Size of cutting plate:	1080 x 736 mm (42 1/2" x 29 3/8")	1472 x 1086 mm (58" x 42-1/4")
Stock range :	0.1 - 2 mm (0.0039" - 0.078")	cardboard 0.2 - 2 mm (0.008" - 0.078") corrugated 0.7 - 4.5mm (0.028" - 0.18")
Max. pressure:	300 tons	400 tons
Max. mechanical speed :	7,500 cycles/hour	5,500 cycles / hour
Main motor :	11 kw (29 Amp)	22 KW (58 Amp)
Other power required:	9 kw (24 Amp)	14 KW (36 Amp)
Overall length:	7018 mm (23')	9880 mm (32' 5")
Overall width:	4189 mm (13' 9")	5270 mm (17' 3")
Overall height:	2045 mm (6' 8")	2580mm (8' 5")
Total weight:	15.5 tons	28 tons

In the interest of product improvement, the manufacturer reserves the right to change specifications and features without notice.